

# Specification Datasheet

## Logi-CHROM

Diode Array Detector 6.1L



### Detection

<b>Detector Type</b>	Diode array detector
<b>Number of Diodes</b>	1024
<b>Pixel Pitch</b>	0.8 nm / diode
<b>Detection Channels</b>	8 (Digital) / 4 (Analog)
<b>Light Source</b>	Deuterium (D <sup>2</sup> ) lamp with integrated GLP chip
<b>Wavelength Range</b>	190 - 1000 nm
<b>Spectral Bandwidth</b>	<3.5 nm at H $\alpha$ line (FWHM) / Note: digital bandwidth 1 - 32 nm
<b>Wavelength Accuracy</b>	$\pm 1$ nm
<b>Noise</b>	$\pm 3.5$ $\mu$ AU at 254 nm (ASTM E1657-98)
<b>Drift</b>	300 $\mu$ AU/h at 254 nm (ASTM E1657-98)
<b>Linearity</b>	> 2.5 AU at 274 nm (ASTM E1657-98)
<b>Maximum Data Rate</b>	100 Hz (LAN) / 12.5 Hz (analog)
<b>Flow Cell</b>	Not included (see Accessories / Spare parts)
<b>Time Constants</b>	0.00 / 0.01 / 0.02 / 0.05 / 0.1 / 0.2 / 0.5 / 1.0 / 2.0 / 5.0 / 10.0 s
<b>Integration Time</b>	Automatic
<b>Wavelength Verification</b>	Internal holmium filter and deuterium lines
<b>Leak Sensor</b>	Yes

## Communication

<b>Inputs</b>	Error (IN), Start (IN), Autozero
<b>Outputs</b>	Events 1 - 2 (Relay and TTL compatible, respectively), Error (OUT), + 5 V, Valve + 24 V, Valve (OUT)
<b>Analog Outputs</b>	4 x 0 - 5 V, 20 bit, offset adjustable
<b>Control</b>	Laura software

## General

<b>Ambient Conditions</b>	Temperature range: 4 - 40 °C, 39.2 - 104 °F, Humidity: below 90 % non-condensing
<b>Power Supply</b>	100 - 240 V, 50 - 60 Hz, 75 W
<b>Dimensions</b>	361 x 158 x 523 mm (W x H x D)
<b>Weight</b>	13.8 kg

## Flow Cell

Part Number	Item
DL-241-28	Flow cell cartridge Pressure Proof, Titanium 10 mm, 10µl, 1/16", 300 bar for Logi-CHROM DAD/MWD

### Europe & Worldwide

**LabLogic Systems Limited**  
Innovation House, 6 Europa View  
Sheffield, S9 1XH, UK

**E-mail:** [solutions@lablogic.com](mailto:solutions@lablogic.com)

**Tel:** +44 (0)114 266 7267

[www.lablogic.com](http://www.lablogic.com)

### USA & Canada

**LabLogic Systems, Inc.**  
3901 Centerview Drive, Suite B  
Chantilly, VA 20151, USA

**E-mail:** [solutions@lablogic.com](mailto:solutions@lablogic.com)

**Tel:** +1-703-429-4209

[www.lablogic.com](http://www.lablogic.com)



Certificate No. 1535  
ISO 9001

**INVESTORS IN PEOPLE**  
We invest in people Gold



Certificate No. 10926  
ISO 9001