

## Flow-RAM<sup>\*\*</sup>

PET/SPECT radio-HPLC Detector



www.lablogic.com

## The innovative, flexible and compliant flow-through detector

LabLogic's PET/SPECT radio-HPLC Detector, the innovative Flow-RAM<sup>™</sup>, is designed to meet the ever increasing demands of the modern nuclear medicine laboratory.

### **Flexibility**

and performance at a glance.

The Flow-RAM<sup>™</sup> is available in a single or dual detector configuration. In the latter configuration, each of the detectors can be set up independent of each other and used for different applications, if required.

With a wide range of detectors suitable for both low and high levels of radioactivity, the Flow-RAM™ is an ideal quality control and research instrument.

## Compliance

As with all LabLogic products, the Flow-RAM<sup>™</sup> has been designed to exceed regulatory requirements. The instrument contains only a power button and display so all detector parameters are controlled via the software method. Used with our industry standard Laura for PET<sup>™</sup> software, the Flow-RAM<sup>™</sup> ensures regulatory compliance via controlled access and audit-trail.

#### A Range of Detectors **NaI Well-type Detector** Suitable for PET, SPECT and High Energy Beta radionuclides across a range of radioactivity levels. 2600.0 -2400.0 -2200.0 -2000.0 -1800.0 -1600.0 -1400.0 -1200.0 for further information **USB** Interface Operating parameters such as high voltage, upper and lower level discriminators as well as power supply and data transfer are all achieved through a USB connection. **Bespoke Lead Shielding** In order to minimise background interference LabLogic provides a range of lead shielding to meet different requirements. Optime Dist <thDist</th> Dist Dist <t commercially available 6 kig 1 Free Fluorine (18F)FDG Unhydrolsed Big 2 3 Peaks Total Area Background Built-in Analog to 99.84 200.00 200.00 **Digital Converter** EXPERIENCE & EXP Fiou-RAM radio-HPLC Detector LabLogic Built-in Analog Users can take an analogue signal EXPERIENCE & EXPERTISE into any third party software. 0 Flow-RAM" **Intelligent Front End Display** Users are able to view instrument parameters **Single Power Button**

www.lablogic.com

Connectivity

The Flow-RAM<sup>™</sup> is compatible with all

HPLC systems.

## **Controlled by** Laura for PET<sup>™</sup>

Flow-RAM<sup>™</sup> control, digital data collection, analysis and reporting is provided by Laura for PET<sup>™</sup>, the industry standard radiochromatography data system developed by LabLogic.



Basic Specifications		
Size	8 (D) x 22 (L) x 23 (W) cm	
Weight	2 kg	
Connectivity	USB	
Please refer to the Technical Specification Sheet		

Please refer to the Technical Specification Sheet

This feature coverts analogue signals from other detectors such as UV, ECD, etc., into digital for use within Laura™, bringing all signals into one place.



## Flow-RAM<sup>™</sup>

## **Dual Flow**-RAM<sup>™</sup>

The Dual Flow-RAM<sup>™</sup> can have up to two detectors connected to it which can be used simultaneously and independently, thus providing maximum flexibility and a two-in-one solution.



radio-HPLC Det	ector Options	
Detector	Radioactivity Type	Commonly Used Isotopes
1" NaI PMT	PET SPECT	F-18, C-11, Ga-68, Rb-82 Tc-99m, In-111
2" NaI PMT	High Energy Gamma	F-18, C-11, Ga-68, Rb-82, Zr-89
Plastic PMT	Beta	Lu-177, Y-90, I-131, Re-188, Re-186
0.1" NaI PMT	Low Energy Gamma	I-125
Well-Type NaI PMT	PET or SPECT with low amounts of activity i.e. small animal imaging applications and measuring low-level impurities.	
PIN Diode	Semi-prep HPLC purificatio	n of radio-tracer after synthesis.
CsI PIN Diode		n and occasionally quality control of ensitive than standard PIN Diode.

# Flow-RAM<sup>™</sup> is controlled by the industry standard radiochromatography software

Flow-RAM<sup>™</sup> control, digital data collection, analysis and reporting is provided by Laura for PET<sup>™</sup>, the industry standard radiochromatography data system developed by LabLogic.

#### Single Software Solution

Laura for PET<sup>™</sup> is a single software solution for the PET/SPECT QC environment. Rather than having to use several software systems, the QC analyst only needs Laura for PET with radio-HPLC, HPLC, radio-TLC, GC and MCA analysis.

#### **Regulatory Compliance**

Laura for PET<sup>™</sup> is designed to meet the regulatory compliance requirements for GMP and FDA 21 CFR Part 11 and FDA 21 CFR Part 212 requirements.

#### Intuitive

Laura for PET<sup>™</sup> is easy to use allowing quick familiarisation with the system and rapid adoption by its users.

#### **Prudent Investment**

From a standalone installation to a full client/server implementation, Laura for PET<sup>™</sup> offers a scalable solution to your data storage requirements. Applications and data can be separated across local clients and central servers to match IT requirements.

ECD

#### **Complete Workflow Solution**

Laura for PET<sup>™</sup> will guide the analyst through the main QC process. Methods can be pre-defined and chosen from a drop down list. Automatic settings provide for automatic peak integration and report printing.

0



#### **Consistent and Secure**

The software allows the user to lock the configuration of methods, reports, etc., to ensure consistency of data capture and presentation.

#### **Digital Signal**

Signals from radiochromatography instruments are reported digitally in counts, CPS and CPM. In addition, the full dynamic range of the detector is processed avoiding limitations commonly seen with analog signals.

#### Half Life Correction

Half life correction function enables users to correct for half life while a run is in progress or post-run, using a reference time and date.

Half Life Correction		
Half Life Correction	·	
No Correction		
Orrect from measurement start		
Correct from	01/01/2009 🗍 🕆 12:00:00 📺	
OK Cancel Apply		

#### Reporting

Relevant values are reported such as % total for radiochemical purity checks. The powerful Report Designer allows you to configure multiple reports and to calculate and present data in real time.

## Service and Support

Users of our systems can benefit from our comprehensive, fully inclusive service and support.

We can give reassurance that if things go wrong or you need expert advice, help is only an e-mail or phone call away.

### **Validation Services**

Our Validation Service enables you to implement and get maximum value from your investments as soon as possible.

We work as a partner with your Quality Manager, System Manager and users to provide a tailored Validation Plan, suited to your needs. Our Validation Specialists who have many years' of experience in GLP system validation, detailed knowledge of our systems, together with other industry standard systems to help you meet company and regulatory requirements.

## Training

LabLogic can provide a variety of training courses and workshops to help you get the most out of your instrument and software.

All training is performed by our expert Product and Support Specialists who have many years experience in the development and use of the instruments and software.

Certificates can be provided to complement your internal GLP training records.



#### Europe & Worldwide

LabLogic Systems Limited Innovation House, 6 Europa View Sheffield, S9 1XH, UK

E-mail: solutions@lablogic.com Tel: +44 (0)114 266 7267 Fax: +44 (0)114 266 3944

www.lablogic.com



USA & Canada

LabLogic Systems, Inc. 1911 N US HWY 301, Suite 140 Tampa, FL 33619, USA

E-mail: solutions@lablogic.com Tel: +1-813-626-6848 Fax: +1-813-620-3708 www.lablogic.com



